



Handling and maintenance

of the BCD 360 Knot Filler applicator

Technical Info

- Applicator for 12 mm sticks.
- Robust and reliable tool.
- 300 watts for greater adhesive output.
- External temperature control from 140 °C to 230 °C.
- Light-weight model.
- Non breakable circular TPR handle for comfortable long hour operation.
- Unique effort-saving trigger.



The tool must be placed on the metal stand.



Never place the heated tool on its side.



Never point the nozzle upwards.

Caution!

The hot nozzle can cause damage and/or burns. After use, allow the gun to cool down completely before storing it. Keep safely and out of reach of children.

► Handling

Please note the following handling points

- ✓ Let the gun heat for 3-4 minutes!
- ✓ Never pull a stick backwards from the gun.
- ✓ Recommended temperature setting 160 °C.
- ✓ Tighten the nozzle regularly.
- ✓ Use only recommended adhesives.
- ✓ Keep the melting chamber free of dirt and dust.
- ✓ Protect the device from moisture and liquids.



External temperature control



Flow adjustment



Ergonomical trigger

► Claims

Important info regarding claims

When we dismantle a tool, we can always see what caused the malfunction. In 99% of the cases, one of the below mentioned points has occurred - they are not valid reasons for a complaint. If you are convinced that none of the points have occurred, we will gladly check the tool in our workshop.

The following errors are not valid reasons for a complaint:

- The gun was placed on its side.
- The nozzle was held upwards for too long.
- The tool was not heated enough before starting.
- A stick was pulled backwards from the gun.
- The temperature was set too high.